




7300 YELLOW ALKYD LOW VOC TRAFFIC MARKING PAINT

Low VOC - Lead Free Yellow

Product Description				Recommended Uses																																															
<p>7300 YELLOW ALKYD TRAFFIC MARKING PAINT is an acetone based, heavy duty marking paint formulated for excellent film build and better resistance to traffic wear and weather. RAE's line of Low VOC Alkyd Marking Paints are designed for commercial use by professional contractors, municipalities and military use.</p> <ul style="list-style-type: none"> Meets Federal Specification A-A-2886(B) Type II Formulated for Brush, Spray, or Roller Ready to Spray - No Reduction Needed <p><i>Note: The United States Environmental Protection Agency (EPA) has determined that ACETONE does not contribute, in any significance, to ozone formation or green house emissions - and has thus made it exempt from VOC regulatory requirements and the federal Clean Air Act.</i></p>				<p>This product has been designed for painting centerlines, edgelines, curbs, highways, airport runways, medians, parking lots, crosswalks, traffic aisles, storage zones, stop zones, auxiliary markings, etc.</p> <p>Use on concrete, asphalt, and brick. Exterior and Interior. Can be used with glass beads for added reflectance. <i>Recommended for restriping of previously painted lines.</i> Available in Yellow, White, Blue, Red, and Black.</p>																																															
Performance Characteristics				Product Characteristics																																															
<p>MEETS FEDERAL SPECIFICATION A-A-2886(B)</p> <table border="1"> <thead> <tr> <th>Test Description</th> <th>Test Method</th> <th>Requirements</th> <th>Results</th> </tr> </thead> <tbody> <tr> <td>Color (yellow)</td> <td>Fed. Std. 595 #33538</td> <td>6 CIE Lab</td> <td>Pass</td> </tr> <tr> <td>Fineness of Grind</td> <td>ASTM D1210</td> <td>3 Hegman min.</td> <td>Pass</td> </tr> <tr> <td>Dry Time No-Pick-Up</td> <td>ASTM D711</td> <td>10 minutes max.</td> <td>Pass</td> </tr> <tr> <td>Flexibility</td> <td>ASTM D522</td> <td>Pass</td> <td>Pass</td> </tr> <tr> <td>Consistency</td> <td>ASTM D562</td> <td>70 - 85 Ku</td> <td>Pass</td> </tr> <tr> <td>Accelerated Package Stability</td> <td>ASTM D1849</td> <td><5 Ku change</td> <td>Pass</td> </tr> <tr> <td>Water Resistance</td> <td>ASTM D1306</td> <td>Pass</td> <td>Pass</td> </tr> <tr> <td>Bleeding Ratio</td> <td>ASTM D969</td> <td>0.90 min</td> <td>Pass</td> </tr> <tr> <td>Dry Opacity</td> <td>Fed-Std-141</td> <td>0.92 min</td> <td>Pass</td> </tr> <tr> <td>Accelerated Weathering</td> <td>ASTM G53</td> <td>Pass</td> <td>Pass</td> </tr> </tbody> </table> <p><i>Note: These results in Performance & Product Characteristics represent actual control values when tested under laboratory conditions. To the best of our knowledge, the above technical data is true and accurate at the date of issuance but is subject to change without prior notice.</i></p>				Test Description	Test Method	Requirements	Results	Color (yellow)	Fed. Std. 595 #33538	6 CIE Lab	Pass	Fineness of Grind	ASTM D1210	3 Hegman min.	Pass	Dry Time No-Pick-Up	ASTM D711	10 minutes max.	Pass	Flexibility	ASTM D522	Pass	Pass	Consistency	ASTM D562	70 - 85 Ku	Pass	Accelerated Package Stability	ASTM D1849	<5 Ku change	Pass	Water Resistance	ASTM D1306	Pass	Pass	Bleeding Ratio	ASTM D969	0.90 min	Pass	Dry Opacity	Fed-Std-141	0.92 min	Pass	Accelerated Weathering	ASTM G53	Pass	Pass	<p>Vehicle Type: Alkyd Blend</p> <p>Viscosity: 80 to 85 Ku</p> <p>Weight Solids: 68.00% minimum</p> <p>Volume Solids: 43.00% minimum</p> <p>Density (Weight per Gallon): 11.35 ± 0.20 lbs/gal</p> <p>VOC (minus exempts): 148 g/L</p> <p>VOC (with exempts): 87 g/L</p> <p>Dry time: No-Pick-Up: < 10 minutes Dry Through: < 25 minutes</p> <p><i>(Note: Applied film thickness, relative humidity and temperature will affect dry time)</i></p> <p>Shelf Life: 12 months if unopened and stored in a cool area.</p> <p><i>This product does not contain mercury, lead, hexavalent chromium, toluene, chlorinated solvents, hydrolysable chlorine derivatives, or carcinogens as defined in 29 CFR 1910.1200.</i></p>			
Test Description	Test Method	Requirements	Results																																																
Color (yellow)	Fed. Std. 595 #33538	6 CIE Lab	Pass																																																
Fineness of Grind	ASTM D1210	3 Hegman min.	Pass																																																
Dry Time No-Pick-Up	ASTM D711	10 minutes max.	Pass																																																
Flexibility	ASTM D522	Pass	Pass																																																
Consistency	ASTM D562	70 - 85 Ku	Pass																																																
Accelerated Package Stability	ASTM D1849	<5 Ku change	Pass																																																
Water Resistance	ASTM D1306	Pass	Pass																																																
Bleeding Ratio	ASTM D969	0.90 min	Pass																																																
Dry Opacity	Fed-Std-141	0.92 min	Pass																																																
Accelerated Weathering	ASTM G53	Pass	Pass																																																
<p>The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. HOWEVER, RAE PRODUCTS & CHEMICALS CORPORATION MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL RAE PRODUCTS & CHEMICALS CORP. BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF RAE PRODUCTS & CHEMICALS CORP. FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY RAE PRODUCTS & CHEMICALS CORP. SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.</p> <p>CAUTION: DANGER! EXTREMELY FLAMMABLE! VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN! BEFORE using this product it is essential that the "Material Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact RAE Products at 1-708-396-1984 or refer to data at www.raeproducts.net</p>																																																			

7300 YELLOW ALKYD LOW VOC TRAFFIC MARKING PAINT

Low VOC - Lead Free Yellow

Preparation	Application										
<p>The surface to be painted must be dry, free of grease and oil and brushed free of loose dirt. Striping paints will not adhere to unclean surfaces. Application equipment must be clean from all previous paint(s).</p>	<p>Mix paint thoroughly before using. Surfaces should be clean and free from dirt and debris. New sealed or asphalt surfaces should be allowed to cure before application. Paint only in dry weather with no forecast for rain. May be applied by a spray machine, roller or brush.</p> <p>Application Rates: Apply at 12-15 mils. wet , 7.5 mils dry Coverage: Approx. 400 linear ft./gal. with a 4" stripe Approx. 90 ft²/gallon (20 gal. = 1 mile @ 4")</p> <p>Glass beads can be broadcast or mixed into paint at a rate of 4 - 6 pounds of beads per gallon. If spraying, do not mix beads directly into paint.</p>										
Thinning											
<p>Thinning is not required, and is not recommended. Dilution can adversely affect film build, appearance and adhesion. DO NOT add gasoline, oil or any other petroleum-based products.</p>											
Drying Times	Application Conditions										
<p>Dry times are dependent upon weather conditions. The warmer the temperature, the faster the paint will cure. Direct sunlight will speed up dry times. For this product, a basic drying schedule is:</p> <p style="text-align: center;">10 min. (walk on), 40 min. (drive on)</p> <p><i>Note: changes in weather conditions (ie. temp. dropping after application, cold surface temp.) can delay above cure times drastically.</i></p>	<p>Recommended application conditions: Apply between 40°F minimum and 90 °F and at least 5 °F above dew point with a relative humidity below 85%. Best if applied at surface and ambient temperatures of 50°F and above.</p>										
Safety Precautions	Application Equipment										
<p>Always refer to the MSDS for Handling and Hazard conditions. Keep away from open flame. Avoid prolonged or repeated contact with skin. Avoid breathing of vapors or spray mist. Do not take internally. Close container after each use. Wear respirator, eye protection and protective clothing when handling.</p> <div style="display: flex; justify-content: space-around; align-items: center;">  <table border="1" data-bbox="524 1430 732 1635"> <tr><td colspan="2">PAINT 3 UN1263 PGII</td></tr> <tr><td>HEALTH</td><td style="text-align: center;">2</td></tr> <tr><td>FLAMMABILITY</td><td style="text-align: center;">3</td></tr> <tr><td>PHYSICAL HAZARD</td><td style="text-align: center;">0</td></tr> <tr><td>PERSONAL PROTECTION</td><td style="text-align: center;"><input checked="" type="checkbox"/></td></tr> </table> </div>	PAINT 3 UN1263 PGII		HEALTH	2	FLAMMABILITY	3	PHYSICAL HAZARD	0	PERSONAL PROTECTION	<input checked="" type="checkbox"/>	<p>Spray Equipment: Always purge spray equipment of cleaning solvent before using this product. Recommended cleaning solvent: Toluene or Acetone</p> <p>Airless Sprayers: Use pressure between 1500-2000 psi - with tip size between .015" - 0.19" (note: use the lowest pressure necessary to achieve a flat edge-line)</p> <p><i>Note: It is recommended to keep separate sprayers for latex and solvent based paints. If the same spray machine is used for both types of paint extra care must be taken to avoid cross-contamination. Latex and solvent based paints are NOT COMPATIBLE.</i></p> <p>Brush: Use Nylon/Polyester Natural Bristle</p> <p>Roller: Use 3/8" Shed-resistant cover with phenolic core</p>
PAINT 3 UN1263 PGII											
HEALTH	2										
FLAMMABILITY	3										
PHYSICAL HAZARD	0										
PERSONAL PROTECTION	<input checked="" type="checkbox"/>										
<p>The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. HOWEVER, RAE PRODUCTS & CHEMICALS CORPORATION MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL RAE PRODUCTS & CHEMICALS CORP. BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF RAE PRODUCTS & CHEMICALS CORP. FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY RAE PRODUCTS & CHEMICALS CORP. SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.</p> <p>CAUTION: DANGER! EXTREMELY FLAMMABLE! VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN! BEFORE using this product it is essential that the "Material Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact RAE Products at 1-708-396-1984 or refer to data at www.raeproducts.net</p>											